

Aluminium TLS Preset Torque Screwdrivers

Torque range from 0.02 to 13.6 N.m

A range of compact aluminium preset torque screwdrivers, each of which delivers the correct torque accurately and repeatedly.

The models in this range include: TLS 0022, Minor, Standard & TLS 1360. Technical details of all models are given on pages 18-21.

All tools are also available with One Way (O/W) clockwise torque and anti clockwise torque.

These durable, versatile and lightweight tools can be used for Assembly, Maintenance and Servicing in any engineering or manufacturing environment.

Slipping Mechanism

Incorrect tightening is impossible

TORQUE

APPLIED FORCE

Minor FH

INDUSTRY SECTORS

Manufacturing



Order Code	Model	Range		Drive	k mm	g	Repeatability	ISO 6789 Class	Colour
		ISO	Imperial						
015200	Minor FH	14-135 cN.m	1.2-12 lbf.in		111	210	+/- 6%	2F	Blue
015205	Minor FH O/W	14-135 cN.m	1.2-12 lbf.in		125	300	+/- 6%	2F	Blue
015600	Standard FH	50-400 cN.m	4.4-36 lbf.in		127	280	+/- 6%	2F	Blue
015605	Standard FH O/W	50-400 cN.m	4.4-36 lbf.in		127	300	+/- 6%	2F	Blue
015890	TLS 1360 FH	2.5-13.6 N.m	22-120 lbf.in		137	325	+/- 6%	2F	Blue
015895	TLS 1360 FH O/W	2.5-13.6 N.m	22-120 lbf.in		137	400	+/- 6%	2F	Blue
015999	Pack of four interchangeable coloured end caps (supplied free with all TLS Screwdrivers except 0022)								

Lightweight, high quality TLS Preset Torque Screwdriver range

- Absolute accuracy and consistency.** Accurate process control is ensured by eliminating under and over tightening due to the proven slipping mechanism
- Ease of use.** Tools can be used by operators at any skill level, due to unique slipping mechanism
- Improved production quality.** Accurate torque application reduces the likelihood of warranty and rework
- Increased production efficiency.** Lightweight aluminium construction and smooth reset action of the tools increase production efficiency by reducing operator fatigue
- Long tool life.** High quality, robust construction
- Operational versatility.** These versatile tools are ideal for a wide range of applications, with wide torque range and one way slipping action option



Standard FH



TLS 1360 FH



Additional features

- TLS range (excluding 0022 range) supplied as standard with a quick converter adaptor to 1/4" male square drive
- For more information on ESD compliant versions. **See page 25**
- Comprehensive range of Accessories, Bits and Blades. **See pages 88-89**
- TLS Screwdrivers can be customised to your exacting requirements. **See page 83**
- TLS Screwdrivers are supplied with a pack of four interchangeable coloured end caps to allow easy identification of what tool is set to what torque value, hence making a job more efficient. (Order Code: 015999) (not supplied with TLS 0022 screwdrivers)

For more information: Tool Selector; gedore-torque.com/tool-selector Telephone; +44 (0) 1483 894 476
Videos; www.youtube.com/gedore-torque Email; salesandrepairs@gedore-torque.com

Want to know how to use this tool?

YouTube

Watch our video