

# Prime Preset Torque Screwdrivers

Torque range from 0.2 to 4.5 N.m

These tools have been specifically designed to provide a low cost product that is suitable for light or occasional use, or one-off applications. Can be used up to 2,000 cycles.

They have no certification and are not intended for regular or heavy use, where our Pro Preset range of preset screwdrivers should be selected.

## Low cost Preset Torque Application Screwdrivers, for one-off applications or light use

Prime Preset Torque Screwdrivers offer a low cost option for applications where a torque tool may not previously have been considered

They combine accuracy with the benefits of a moulded plastic body and ergonomic design, to remove the risk of under or over tightening. As well as the application of torque, they can also undo fasteners, as One Way (O/W) action is standard

A comprehensive range of Accessories, Bits and Blades is available.  
**See pages 88-89**



**Slipping Mechanism**  
Incorrect tightening is impossible



Prime 150



Prime 450

**For more information:** Tool Selector; [gedore-torque.com/tool-selector](http://gedore-torque.com/tool-selector) Telephone; +44 (0) 1483 894 476  
Videos; [www.youtube.com/gedore-torque](http://www.youtube.com/gedore-torque) Email; [salesandrepairs@gedore-torque.com](mailto:salesandrepairs@gedore-torque.com)

Want to know how to use this tool?  
**YouTube**  
Watch our video

| Order Code | Model        | Range         |                 | Drive | k mm | g   | Repeatability |
|------------|--------------|---------------|-----------------|-------|------|-----|---------------|
|            |              | ISO           | Imperial        |       |      |     |               |
| 065100     | Prime 150 FH | 0.2 - 1.5 N.m | 1.8 - 13 lbf.in | 1/4"  | 138  | 198 | +/- 10%       |
| 065200     | Prime 450 FH | 0.5 - 4.5 N.m | 4.5 - 40 lbf.in | 1/4"  | 138  | 198 | +/- 10%       |