

MTP & MTS Mechanical Torque Testers

Torque range from 0 to 25 N.m

Mechanical Torque Calibration Analysers that can be used in a many different situations to provide accurate measurement of torque values for hand-operated Torque Tools. These testers are portable, robust and do not require power.

MTP & MTS Mechanical Torque Testers

MTP 10 & MTS 35, 130, 400, 1200 & 2500

Accurate measurement. Designed to monitor low torque values for Hand operated Torque Tools, providing +/-2% accuracy

Ease of use. Perfect for use by operators of any skill level, as the robust design eliminates the fear of damage caused by overloading

Fast results. The MTS Testers are designed to quickly give confidence that your Torque Tools are operating within limits. The easy to read analogue dial, peak torque and limit pointers all work together to give the operator instant confirmation of tool performance

Long tool life. High quality and robust design, with a two year warranty

End Fittings. Compatible with Setting adaptors see page 84

Versatile. Able to operate in a wide variety of environments and situations from shop floor to field operations as the MTS and MTP have no requirement for power

Servicing. Regular servicing is essential to ensure precision and consistent accuracy



For more information: Tool Selector; gedore-torque.com/tool-selector Telephone; +44 (0) 1483 894 476
Videos; www.youtube.com/gedore-torque Email; salesandrepairs@gedore-torque.com

Want to know how to use this tool?
YouTube
Watch our video

Order Code	Model	ISO	Calibrated Range			Drive	kg	Accuracy
				Imperial				
058100	MTP 10	0-10 cN.m	0.5 cN.m	0-14 ozf.in	1 ozf.in		0.98	+/- 2%
058110	MTS 35	7-35 cN.m	0.5 cN.m	10-50 ozf.in	0.5 ozf.in		3.20	+/- 2%
058120	MTS 130	26-130 cN.m	2 cN.m	36-180 ozf.in	2 ozf.in		3.20	+/- 2%
058130	MTS 400	0.8-4 N.m	0.05 N.m	7-36 lbf.in	0.5 lbf.in		3.20	+/- 2%
058140	MTS 1200	2.4-12 N.m	0.2 N.m	24-120 lbf.in	2 lbf.in		3.20	+/- 2%
058150	MTS 2500	5-25 N.m	0.5 N.m	44-220 lbf.in	5 lbf.in		3.20	+/- 2%