

95
1

Cable Shears with twin cutting edge

(PATENTED)



95 11 200



95 12 200



95 16 200



95 17 200



The twin cutting edge allows a comfortable handle position in all cutting situations within the specified cutting capacity.

- for cutting copper and aluminium cables
- not suitable for steel wire and hard drawn copper conductors
- precision ground, hardened blades
- clean and smooth cut without crushing and deformation
- by dividing the cutting actions into initial cut (insulating sheath in the front cutting area) and final cut (conductor in the back cutting area), cables up to Ø 20 mm can be cut in one-hand operation
- less effort required due to favourable lever ratio and optimised cutting-edge geometry
- guard prevents operators' fingers being pinched
- adjustable bolted joint, self-retaining screw
- High-grade special tool steel, forged, oil-hardened



Initial cut: using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width.



Final cut: after cutting the sheath in the front profile the conductors in the rear part are cut. Initial cut in the front profile, final cut in the rear profile – to keep it as easy as possible.

Article No.	EAN 4003773-	↔ mm		Tool	Handles	Cutting capacities		AWG	g
						Ø mm	mm ²		
95 11 200	043928	200		burnished	plastic coated	20	70	2/0	283
95 12 200	047834	200		burnished	with multi-component grips	20	70	2/0	324
95 16 200	026761	200	⚠ 1000V	chrome plated	insulated with multi-component grips, VDE-tested	20	70	2/0	340
95 17 200	026952	200	⚠ 1000V	chrome plated	handles with dipped insulation, VDE-tested	20	70	2/0	360