

95
32

Cable Shears (ratchet action)

with telescopic handles



95 32 038



Handles adjustable in length and angular position for easier work: set the handle length to the optimum lever for powerful cutting; put the handles at an angle for a comfortable gripping position

Cable shears with adjustable telescopic handles allowing angular positioning

- for cable diameters up to 38 mm, handles can be positioned at an angle to set the optimum handle width, which makes the shear also suitable for work in confined areas
- comfortable work thanks to ratchet action and low weight
- heavy duty telescopic handles made of oval aluminium tubing; extendable up to 770 mm for maximum leverage on large cable diameters; retractable down to 570 mm for minimum space requirements during transport
- replaceable cutting head
- extensive cutting range up to max. Ø 38 mm or max. 280 mm² (e.g. 4 x 70 mm² NYY) in copper and aluminium cables
- easier, neater cut due to optimised cutting-edge geometry
- adjustable bolted joint
- cutting head: special quality high-grade tool steel, oil-hardened
- handles: high-strength oval aluminium tubing



Setting of a favourable handle width



After the first partial cut, the handles open by ratchet action



Repeat cutting and opening actions until the cable is cut through

with adjusting button



570 mm
620 mm
670 mm
720 mm
770 mm

Article No.	EAN	↔ mm		Head	Handles	Cutting capacities		MCM	g
						Ø mm	mm ²		
95 32 038	4003773-071556	570		burnished	with multi-component grips	38	280	550	1980

95 39 038 073260 Spare cutter head for 95 32 038

95
32

Cable Cutters (ratchet action)

with telescopic handles



95 32 060



with adjusting
button



- for copper and aluminium single conductors as well as multiple stranded cables - also with hard rubber or plastic sheath
- not suitable for steel wire and wire ropes
- also suitable for cables with iron sheath reinforcement
- little hand force required for cutting due to optimum transmission ratio
- high cutting capacity due to two-hand operation and ratchet action
- the blade can be opened in any cutting position
- blade: special-quality high-grade tool steel, oil-hardened
- handles: high-strength oval aluminium tubing
- handle length with multiple position adjustment from 400 - 610 mm (short transport length, individual adaptation to working conditions)

95 32 060

tool length: 600 - 810 mm; weight only 3820 g

95 32 100

tool length: 650 - 860 mm; weight only 4980 g



Article No.	EAN	↔ mm		Head	Handles	Cutting capacities			⚖ g
						Ø mm	mm²	MCM	
95 32 060	071563	600		burnished	with multi-component grips	60	740	1400	3820
95 32 100	071570	650				100	960	1900	4980

95 39 720 025290 Movable spare blade for 95 31 720 / 95 32 060

95 39 870 025306 Movable spare blade for 95 31 870 / 95 32 100