

99
1

High Leverage Concreters' Nippers

high lever transmission

DIN ISO 9242



99 10 250



99 10 300



99 11 300



99 14 250



99 14 300



25 % less effort required compared to conventional concreters' nippers of the same size

Extra-slim form for tying deep mounted steel rods

- to lace concrete reinforcing steel with binding wire from a roll
- wire is twisted and cut in a single pass
- high-leverage joint, minimising strain, even when thick binding wires are used
- the high damping of the cutting stroke on cutting through the binding wire reduces the strain on tendons and muscles
- cutting edges additionally hardened; cutting edge hardness approx. 61 HRC
- High-grade special tool steel, forged, oil-hardened



Article No.	EAN 4003773-	↔ mm		Pliers	Head	Handles	Cutting capacities		Head width mm	⚖ g
							Ø mm	Ø mm		
99 10 250	071396	250		black atramentized	polished		3.3	1.8	23.0	350
99 10 300	022398	300	✓				3.8	2.0	25.0	501
99 11 250	071402	250		black atramentized	polished	plastic coated	3.3	1.8	23.0	350
99 11 300	042365	300	✓				3.8	2.0	25.0	537
99 14 250	071419	250		nickel plated			3.3	1.8	23.0	350
99 14 300	028116	300	✓				3.8	2.0	25.0	499